

SFAIRA ONE

GNSS RECEIVER

An Entry-Level Network RTK Rover With Professional Performance



POCKET SIZE & 16HRS BATTERY

Especially made for CORS users, the Sfaira One is designed as small as possible while retaining the necessary functionality. Pocket-sized and lightweight, you can easily take it anywhere. 16hrs of battery life keeps you from power outages, which can also be charged via the Type-C port using a power bank.

CENTIMETER ACCURACY

Designing for smaller size doesn't mean sacrificing GNSS performance. The Sfaira One GNSS receiver is equipped with a high-precision GNSS engine, which can simultaneously track GPS, BDS, GLONASS, Galileo & QZSS, providing stable and accurate centimeter-level positioning in various environments.

CONNECT, LOGIN, SURVEY

Connected via Bluetooth, the Sfaira One receiver can login your CORS account smoothly from your smart phone. Then you can directly start point survey, point stakeout, CAD stakeout and other tasks through SingularPad/SingularSurv field software. The IP65 protection of Sfaira One allows flexible operation in all weather conditions.

SATELLITES TRACKING

Channels	1408
BDS	B1I, B2I, B3I, B1C, B2a, B2b ¹
GPS	L1 C/A, L1C ¹ , L2P, L2C, L5
GLONASS	L1, L2, L3 ¹
Galileo	E1, E5a, E5b, E6 ¹
QZSS	L1, L2, L5
Cold start	<30s
Warm start	<20s
RTK initialization time	<5s (typical)
RTK initialization reliability	>99.9%
Re-acquisition	<1s

ACCURACY

Standalone	1.5m Horizontally 2.5m Vertically
DGPS	0.4m Horizontally 0.8m Vertically
RTK	8mm+1ppm Horizontally 15mm+1ppm Vertically

DATA FORMAT

Positioning data format	NMEA-0183
Correction data format	- RTCM v3.3/3.2/3.1/3.0
Data protocol	Ntrip
Data update rate	1 Hz
Baud rate	115200 bps

COMMUNICATION

Bluetooth	BT2.0
Interface	Type-C, for charging and firmware upgrade

ELECTRICAL

Power consumption	1.0 W
Input voltage	5V DC ≤ 2A
Battery	4800 mAh - 2 hours fast charge - 16 hours working time, with continuous Bluetooth transmission, satellite tracking and RTK surveying

PHYSICAL

Size	Φ50 mm × 149 mm
Weight	409g
Button	1 power button
Indicator	2 LEDs, indicating satellite tracking and battery status

ENVIRONMENTAL

Working temperature	-45 °C to + 75 °C
Storage temperature	-55 °C to + 85 °C
Waterproof & dustproof	IP65
Drop	Designed to survive a 1.5m drop onto concrete

1. BDS B2b, GPS L1C, GLONASS L3 and Galileo E6 signals are reserved for future upgrade.

All specifications are subject to change without notice.

©2023 SingularXYZ Intelligent Technology Ltd. All rights reserved. SingularXYZ[®] is the official trademark of SingularXYZ Intelligent Technology Ltd., registered in People's Republic of China, EU. All other trademarks are the property of their respective owners.